

Measurement Unlimited by The Imagination.

Portable Ultrasonic Flowmeter

UFP-20



intelligent
DIGITAL

Features

1. Multi-flow Measurement Function

Easy configurable for 2-channel or 2-path measurement

2. Energy Meter Function

Energy flow rate measurement with Pt-100 RTD option

3. Receiving-echo Monitor Function

Visual confirmation whether receiving echo is "Good" or "No good"

4. Weather-proof structure IP65

IP65 rating maintained even during measurement

5. USB Memory Data Transfer

Logged data in UFP-20 can be transferred via USB memory device to a PC.


Specifications

Measurement	Method	Ultrasonic pulse transit time difference method		
	Diameter Range	DN 13mm ~ 5000mm		
	Accuracy	Pipe Diameter	Velocity \geq 1m/s	Velocity < 1m/s
		DN 13mm (*2) ~ 90mm (DN 20mm ~ 50mm) (*1)	$\pm 2.0\%$ R.D. ($\pm 2.0\% \sim \pm 5.0\%$) (*1)	$\pm 0.02\text{m/s}$ R.D. ($\pm 0.02\text{m/s} \sim \pm 0.05\text{m/s}$) (*1)
DN 100mm ~ 250mm DN 300mm ~ 5000mm		$\pm 1.5\%$ R.D. $\pm 1.0\%$ R.D.	$\pm 0.015\text{m/s}$ $\pm 0.01\text{m/s}$	
Transducer	Applicable Diameter	Applicable Temperature		
	Small Transducer	DN 13mm ~ 50mm	-20°C ~ 120°C	
	Medium Transducer	DN 65mm ~ 500mm (DN 20mm ~ 50mm) (*1)	-20°C ~ 120°C	
	Large Transducer	DN 300mm ~ 5000mm	-20°C ~ 80°C	
	Cable Length	7m as standard (157m Max. Extendable)		
Output	Analog Output	1port; 4 - 20mA Allowable load resistance 550Ω Max.		
Temperature Input	4pcs of RTD (Pt - 100) as Max.			
Data Logging	Internal logged data transferred through USB memory in CSV format			
Function	EASY interfacing with Installation Wizard Self - diagnostics Low flow cut Zero shift Span compensation 2 - channel / 2 - path measurement (with additional pair of transducers) Thickness meter function (Range; 1mm ~ 100mm / Accuracy; $\pm 0.1\text{mm}$ or $\pm 1.5\%$ R.D.)		Sonic Velocity measurement function (Range; 500m/s ~ 3000m/s / Accuracy; $\pm 5\%$) Filtering Echo - wave form monitor Multi - language support (English, French, German, Italian, Portuguese, Russian, Spanish, Turkish) Metric / English (inch, gallon or barrel) units selectable	
Protection degree	IEC 60529 Protection Degree IP65 (Main Unit and Transducers)			
Internal Battery	8 hours as Max. / Rapid charging 4 hours			

(*1): Medium transducer is recommended for measurement of DN 20mm ~ 50mm pipe which attenuates sonically like Zinc - coated - pipe.

(*2): Site calibration will be required.

Design and specifications are subject to change without prior notice, and without any obligation on the part of the manufacturer.



TOKYO
KEIKI

TOKYO KEIKI INC.

Measurement Systems Company

Head Office

2-16-46, Minami-Kamata, Ohta-ku, Tokyo 144-8551 JAPAN TEL. +81-3-3737-8664 FAX. +81-3-3737-8665

www.tokyo-keiki.co.jp/ryutai/